



# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/09/2017 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : X4-1000 10W-50 Engine Oil

#### 1.2. Recommended use and restrictions on use

Recommended use : Lubricant  
Restrictions on use : No additional information available

#### 1.3. Supplier

Maverick Performance Products  
5950 S. Cooper Rd, Ste 3  
Chandler, AZ 85249  
T 480-621-7302  
[www.vplubricants.com](http://www.vplubricants.com)

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 Toll-Free USA/CAN

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Not classified

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labelling

No labelling applicable

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

2.45% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
2.45% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
2.45% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS-No.) 64742-54-7	0 - 60	Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	(CAS-No.) 68037-01-4	0 - 50	Asp. Tox. 1, H304
10-ethyl-7,9-dimethyl-8-pentylheptadecane; 10-ethyl-8-heptyl-7,9-dimethylnonadecane	(CAS-No.) 163149-28-8	0 - 50	Asp. Tox. 1, H304
10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane	(CAS-No.) 151006-60-9	0 - 50	Asp. Tox. 1, H304
Lubricating oils, petroleum, hydrotreated spent	(CAS-No.) 64742-58-1	0 - < 20	Acute Tox. 4 (Inhalation:dust,mist), H332

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Reactivity : No dangerous reactions known.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Use personal protective equipment as required.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment. Section 8: personal protective equipment.

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool well ventilated place.

Incompatible products : Strong bases. Strong acids. Strong oxidizers.

Incompatible materials : Sources of ignition. Direct sunlight.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

1-Decene, homopolymer, hydrogenated (68037-01-4)		
Not applicable		
10-ethyl-7,9-dimethyl-8-pentylheptadecane; 10-ethyl-8-heptyl-7,9-dimethylnonadecane (163149-28-8)		
Not applicable		
10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane (151006-60-9)		
Not applicable		
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Lubricating oils, petroleum, hydrotreated spent (64742-58-1)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.

Environmental exposure controls : Prevent leakage or spillage.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Avoid all unnecessary exposure.

##### Hand protection:

Wear suitable gloves resistant to chemical penetration. nitrile rubber gloves

##### Eye protection:

Chemical goggles or safety glasses

##### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved respirator

##### Other information:

Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Colour : amber  
Odour : petroleum

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: >= 85.9 cSt @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>1-Decene, homopolymer, hydrogenated (68037-01-4)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg
<b>10-ethyl-7,9-dimethyl-8-pentylheptadecane; 10-ethyl-8-heptyl-7,9-dimethylnonadecane (163149-28-8)</b>	
LD50 oral rat	> 5000 mg/kg
<b>10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane (151006-60-9)</b>	
LD50 oral rat	> 5000 mg/kg
<b>Distillates (petroleum), hydrotreated heavy paraffinic (DMSO &lt; 3%) (64742-54-7)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Lubricating oils, petroleum, hydrotreated spent (64742-58-1)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 4480 mg/kg
LC50 inhalation rat (mg/l)	2.18 mg/l
ATE US (vapours)	2.18 mg/l/4h
ATE US (dust,mist)	2.18 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Likely routes of exposure : Inhalation. Skin and eye contact.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>1-Decene, homopolymer, hydrogenated (68037-01-4)</b>	
LC50 fish 1	> 750 mg/l
EC50 Daphnia 1	190 mg/l
NOEC (acute)	1000 mg/l

<b>Distillates (petroleum), hydrotreated heavy paraffinic (DMSO &lt; 3%) (64742-54-7)</b>	
EC50 Daphnia 1	> 10000 mg/l

<b>Lubricating oils, petroleum, hydrotreated spent (64742-58-1)</b>	
LC50 fish 1	3.2 - 79.6 mg/l

### 12.2. Persistence and degradability

<b>X4-1000 10W-50 Engine Oil</b>	
Persistence and degradability	Not established.

<b>1-Decene, homopolymer, hydrogenated (68037-01-4)</b>	
Persistence and degradability	Readily biodegradable.

### 12.3. Bioaccumulative potential

<b>X4-1000 10W-50 Engine Oil</b>	
Bioaccumulative potential	Not established.

<b>1-Decene, homopolymer, hydrogenated (68037-01-4)</b>	
Bioaccumulative potential	Not expected to bioaccumulate.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated.

#### Transport by sea

Not regulated.

#### Air transport

Not regulated.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

##### 10-ethyl-7,9-dimethyl-8-pentylheptadecane; 10-ethyl-8-heptyl-7,9-dimethylnonadecane (163149-28-8)

EPA TSCA Regulatory Flag

P - P - indicates a commenced PMN substance.  
XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

##### 10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane (151006-60-9)

EPA TSCA Regulatory Flag

P - P - indicates a commenced PMN substance.  
XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

#### 15.2. International regulations

##### CANADA

##### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### 10-ethyl-7,9-dimethyl-8-pentylheptadecane; 10-ethyl-8-heptyl-7,9-dimethylnonadecane (163149-28-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### 10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane (151006-60-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### EU-Regulations

##### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### National regulations

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

#### Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on Taiwan National Chemical Inventory  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)

#### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on Taiwan National Chemical Inventory  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists).  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
OSHA 29CFR 1910.1200 Hazard Communication Standard.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H304	May be fatal if swallowed and enters airways
H332	Harmful if inhaled

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average


# VP Lubricants X4-1000 10W-50 Engine Oil

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*