

# SAFETY DATA SHEET

Issuing Date 06-Feb-2019

Revision Date 16-June-2020

Revision Number 5



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance, and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name VP Foam Filter Oil (VP7950020)

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Oil for Foam Air Filters Aerosol

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Maverick Performance Products

Supplier Address 5950 S Cooper Road  
Chandler, AZ. 85249

Supplier Phone Number Phone: (480) 621-7302

### Emergency telephone number

INFOTRAC North America (480) 621-7302

INFOTRAC International (480) 621-7302

Company Emergency Phone Number (480) 621-7302

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).


Skin corrosion/irritation	Category 2
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2



Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Liquefied gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

<b>Signal word</b>	<b>Danger</b>
<b>Hazard Statements</b> Causes skin irritation May cause cancer Suspected of damaging fertility or the unborn child May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated	
	
<b>Appearance</b> Red	<b>Physical state</b> Liquid spray Aerosol
	<b>Odor</b> Aliphatic hydrocarbons

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands, and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Pressurized container: Do not pierce or burn, even after use  
 Do not spray on an open flame or other ignition source

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)

#### Skin

IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place  
Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

18.825 % of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Harmful to aquatic life with long lasting effects  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	15 - 40	*
Propane	74-98-6	10 - 30	*
Hexanes	110-54-3	10 - 30	*
Paraffin oils, petroleum, catalytic dewaxed light	64742-71-8	1 - 5	*
Supplier Trade Secret	Trade Secret	1 - 5	*
Cyclohexane	110-82-7	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Skin contact**

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

**Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

**Ingestion**

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

**Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use extinguishing agent suitable for type of surrounding fire. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists. Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or water spray.

**Unsuitable extinguishing media**

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**Specific hazards arising from the chemical**

Some may burn but none ignite readily. Ruptured cylinders may rocket.

**Uniform Fire Code**

Irritant: Liquid  
Aerosols: Level III

**Hazardous Combustion Products**

Carbon oxides.

**Explosion Data**

**Sensitivity to Mechanical Impact** Yes.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Stop leak if you can do it without risk.

**Other Information** Ventilate the area.

### Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for cleaning up** Do not direct water at spill or source of leak.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Do not puncture or incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact with eyes. Keep away from open flames, hot surfaces and sources of ignition.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from moisture. Keep out of the reach of children. Store away from other materials. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Hexanes 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m <sup>3</sup>	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>
Cyclohexane 110-82-7	TWA: 100 ppm	TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup> (vacated) TWA: 300 ppm (vacated) TWA: 1050 mg/m <sup>3</sup>	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical state</b>	Liquid spray, Aerosol	<b>Odor</b>	Aliphatic hydrocarbons
<b>Appearance</b>	Red	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN		
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			



<b>Upper flammability limit</b>	No data available	
<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Specific Gravity</b>	0.78	
<b>Water Solubility</b>	Insoluble	
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No information available	
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known
<b>Explosive properties</b>	No data available	
<b>Oxidizing properties</b>	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks. Excessive heat.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Strong bases.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Product Information



<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Irritating to eyes. (based on components). May cause redness, itching, and pain. May cause irritation.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5530 mg/m <sup>3</sup> ( Rat ) 4 h
Propane 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
Hexanes 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h
Supplier Trade Secret	> 2000 mg/kg ( Rat )	> 4480 mg/kg ( Rabbit )	-
Cyclohexane 110-82-7	= 12705 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 9500 ppm ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	A2	Group 1	Known	X
Paraffin oils, petroleum, catalytic dewaxed light 64742-71-8	A2	Group 1	Known	X

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans



**NTP (National Toxicology Program)***Known - Known Carcinogen***OSHA (Occupational Safety and Health Administration of the US Department of Labor)***X - Present*

<b>Reproductive toxicity</b>	Contains a known or suspected reproductive toxin.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
<b>Chronic Toxicity</b>	Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects.
<b>Target Organ Effects</b>	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Peripheral Nervous System (PNS). Lungs.
<b>Aspiration Hazard</b>	May be fatal if swallowed and enters airways.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (dermal)**

13,947.60 mg/kg (ATE)

**ATEmix (inhalation-vapor)**

786.50 ATEmix

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)		48h EC50: > 1000 mg/L
Hexanes 110-54-3		96h LC50: 2.1 - 2.98 mg/L (Pimephales promelas)		24h EC50: > 1000 mg/L
Cyclohexane 110-82-7	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: 3.96 - 5.18 mg/L (Pimephales promelas) 96h LC50: 48.87 - 68.76 mg/L (Poecilia reticulata) 96h LC50: 24.99 - 44.69 mg/L (Lepomis macrochirus) 96h LC50: 23.03 - 42.07 mg/L (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	24h EC50: > 400 mg/L

### Persistence and Degradability

No information available.

### Bioaccumulation

Chemical name	Log Pow
Propane 74-98-6	2.3
Cyclohexane 110-82-7	3.44

### Other adverse effects

No information available.

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
<b>Contaminated Packaging</b>	Dispose of contents/containers in accordance with local regulations.
<b>US EPA Waste Number</b>	D001 U056
<b>California Waste Codes</b>	331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Hexanes 110-54-3	Toxic Ignitable
Cyclohexane 110-82-7	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

<b>Proper Shipping Name</b>	CONSUMER COMMODITY
<b>Hazard Class</b>	ORM-D
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to DOT
<b>Description</b>	CONSUMER COMMODITY, ORM-D
<b>Emergency Response Guide Number</b>	126

#### TDG

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Description</b>	UN1950, AEROSOLS, 2.1

#### MEX

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Description</b>	UN1950, AEROSOLS, 2.1

#### ICAO

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Description</b>	UN1950, AEROSOLS, 2.1

#### IATA

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS, FLAMMABLE



<b>Hazard Class</b>	2.1
<b>ERG Code</b>	10L
<b>Description</b>	UN1950, AEROSOLS, FLAMMABLE, 2.1

**IMDG/IMO**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>EmS-No.</b>	F-D, S-U
<b>Marine Pollutant</b>	This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
<b>Description</b>	UN1950, AEROSOLS (HEXANES), 2.1, MARINE POLLUTANT

**RID**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Classification code</b>	5F
<b>Description</b>	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>ADR/RID-Labels</b>	2.1

**ADR**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Classification code</b>	5F
<b>Tunnel restriction code</b>	(D)
<b>Description</b>	UN1950, AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS

**ADN**

<b>UN-No.</b>	UN1950
<b>Proper Shipping Name</b>	AEROSOLS
<b>Hazard Class</b>	2.1
<b>Classification code</b>	5F
<b>Special Provisions</b>	190, 327, 344, 625
<b>Description</b>	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>Hazard Labels</b>	2.1
<b>Limited Quantity</b>	1 L
<b>Ventilation</b>	VE01, VE04

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA	Not determined
DSL	Not determined
IECSC	

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372



Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Hexanes - 110-54-3	110-54-3	10 - 30	1.0
Cyclohexane - 110-82-7	110-82-7	0.1 - 1	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cyclohexane 110-82-7	1000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Hexanes 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Cyclohexane 110-82-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Hexanes - 110-54-3	Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4					X
Propane 74-98-6	X	X	X		
Hexanes 110-54-3	X	X	X	X	X
Paraffin oils, petroleum, catalytic dewaxed light 64742-71-8		X			X
Cyclohexane 110-82-7	X	X	X	X	

**International Regulations****Mexico****National occupational exposure limits**

Chemical name	Carcinogen Status	Exposure Limits
Petroleum distillates, solvent-refined heavy paraffinic	A2	
Hexanes		Mexico: TWA 50 ppm Mexico: TWA 176 mg/m <sup>3</sup>



		Mexico: STEL 1000 ppm Mexico: STEL 3500 mg/m <sup>3</sup>
Paraffin oils, petroleum, catalytic dewaxed light	A2	
Cyclohexane		Mexico: TWA 300 ppm Mexico: TWA 1050 mg/m <sup>3</sup> Mexico: STEL 375 ppm Mexico: STEL 1300 mg/m <sup>3</sup>

A2 - Suspected Human Carcinogen  
Mexico - Occupational Exposure Limits - Carcinogens

**Canada**  
**WHMIS Hazard Class**  
Not determined

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards</b> 2 *	<b>Flammability</b> 4	<b>Physical Hazard</b> 0	

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Maverick Performance Products  
5950 S Cooper Road  
Chandler, AZ 85249  
(480) 621-7302

**Issuing Date** 06-Feb-2019  
**Revision Date** 16-June-2020  
**Revision Note** No information available

**Disclaimer**  
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

